


Rating :
 15A 250V AC UL cUL
 10A 250V AC VDE 3C KC

Insert And Extract Force: 20N~50N
 Terminal Strength: ≥60N
 Operating Life: ≥6000 cycles
 Withstand Voltage: Between all terminals:2500VAC (50-60Hz)1min
 terminals to Base:3750V AC (50-60Hz)1min
 Leakage Current : 1mA

Insulation Resistance: ≥100MΩ 500V DC
 Body Materil: PBT 94V-2~0

46*46*24.5cm箱, 100只*20袋装=2K件, 净重:17.4 KG, 毛重:19.4=KG,

序号	名称	材料	处理	数量	备注
1	DB-14-1 (2PIN) 基座	PBT	黑色	1	
2	DB-14-FS短插销	黄铜	镀锡	2	Plating Thickness 40u" -80u"

A4				普通公差: COMMON TOLERANCE :		 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONI CS CO., LTD.							
A3				UP TO 5 ±0.20								单位	mm
A2				ABOVE 5 TO 30 ±0.30		绘图	金泽杰	核对	张龙	型号	/DB-14		
A1				ABOVE 30 ±0.50		日期	2022/2/17	核准	同培雷	料号	DB-14-1F (2PIN)-ZP		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	±5°	日期	2022/2/17	核准	同培雷	料号	DB-14-1F (2PIN)-ZP		