






P.C.B LAYOUT MOUNTING PATTERN

SPECIFICATIONS

Electrical:


- 1.Rating: 1.5A , 30V AC
- 2.Contact Resistance: 30 mΩ Max
- 3.Dielectric Withstanding Voltage: 500 V AC
- 4.Insulation Resistance: 1,000 MΩ Min
- 5.Operating Temperature: -35℃ ~ 85℃

Material:

- 1.Housing: LCP
- 2.Contact: Phosphor Bronze
- 3.Shell: Brass / Spcc

Finish:

- 1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall
- 2.Shell: Nickel under Plated surface layer



SUA-110M7Ax-x-S236

Shell Material :

Blank : BRASS

I : SPCC

COLOR :

Black: B

White : W



东莞市溪榜电子有限公司

Switch Connector DONG GUAN XI BANG ELECTRONICS CO., LTD

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5 ±0.2


Above 5 ~ 15 ±0.3

Above 15 ~ 30 ±0.4

Above 30 ~ 50 ±0.5

Angle ±0.3

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L		TITLE	CONNECTOR
Jack Lu	05/03/22				
CHECKED BY:	DATE	FINISH		MODLE	USB AF SMT 無後蓋外殼彎角 反向
Jacky Chen	05/03/22				
APPROVED BY:	DATE	SCALE	1 : 1	DWG NO.	SUA-110M7Ax-x-S236
Tony Kao	05/03/22	SHEET NO.	1 of 1	PART NO.	SUA-110M7Ax-x-S236
					SIZE A4
					VER R2