



RECOMMENDED PCB LAYOUT
T=1.2MM, TOLERANCES ±0.05MM

NOTE:

1. MATERIAL:
 - 1.1 HOUSING: PA9T, UL 94V-0
 - 1.2 TERMINAL: Phosphor Bronze
2. FINISH:
 - 2.1 TERMINAL: NICKEL 50 μm MIN UNDER PLATED OVERALL, Au PLATED ON THE CONTACT AREA. OR Tin ON THE SOLDERING AREA.
3. PRODUCT SPECIFICATION
 - 3.1 CURRENT RATING :5A
 - 3.2 VOLTAGE RATING : 30V AC
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE:500VAC
 - 3.4 INSULATION RESISTANCE: 100MΩ min.
 - 3.5 CONTACT RESISTANCE: 30mΩ Max.
 - 3.6 Operating Temperature: -40° ~105°

XG 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

UNLESS OTHERWISE SPECIFIED, TOLERANCE: X. iΔ0.5 X.x iΔ0.35 X.xx iΔ0.25 ANGULAR iΔ218	DESIGN	PENG. GAO	DATE	TITLE: XB-B01F-A-L1-14P	
	APPROVED	FEI. LONG. HE	DATE	REV: 01	SCALE: 1:1
	PART NO			UNIT: MM	
	DRAWING NO			SIZE: A4	SHEET: 1/1