



SUA-110M1A-30x-S277

鍍層厚度：

Blank : 1u"
2 : 15u"
3 : 30u"

RECOMMENDED PCBA LAYOUT

SPECIFICATIONS:

- 1.ELECTRICAL CHARACTERISTICS;
- 1.1 CONTACT RESISTANCE: 30mΩ MAX
- 1.2 DIELECTRIC WITHSTANDING VOLTAGE: 100 V 1 min
- 1.3 INSULATION RESISTANCE: 100 MΩ MIN
- 1.4 OPERATING TEMPEROTURE: -25℃ ~ 85℃
- 2.MATERIAL:
- 2.1 HOUSING: LCP , Color:Blue
- 2.2 CONTACT: PHOSPHOR BRONZE
- 2.3 SHELL: BRASS
- 3.PLATING:
- 3.1 CONTACT: PLATED GOLD IN MATING AREA ;
TIN PLATED ON SOLDER BALLS ;
NICKEL UNDER PLATED OVERALL
- 3.2 SHELL: NICKEL UNDER PLATED SURFACE LAYER



东莞市溪榜电子有限公司


DONG GUAN XI BANG ELECTRONICS CO., LTD

Switch Connector

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

1	新增膠芯顏色	Jack	010522
ITEM NO.	DESCRIPTION	DRAWN	DATE

DRAWN BY:	DATE	MAT'L		TITLE	CONNECTOR
Jack Lu	01/05/22	FINISH		MODLE	USB 3.0 AF SMT 沉板3.5mm 無捲邊
CHECKED BY:	DATE	SCALE	1 : 1	DWG NO.	SUA-110M1A-30x-S277
Jacky Chen	01/05/22	SHEET NO.	1 of 1	PART NO.	SUA-110M1A-30x-S277
APPROVED BY:	DATE				
Tony Kao	01/05/22				