

ROHS

Top view of the component. The overall width is 14.30. The distance between the center of the first and last pins is 1.2. The distance between the center of the first and last pins, excluding the end pins, is 0.6. The component is labeled with 'ON' and 'X3'. The pins are numbered 1 through 10. The distance between the center of the first and last pins, excluding the end pins, is 0.6.

Side view of the component. The overall height is 0.05. The distance between the center of the first and last pins is 0.4. The distance between the center of the first and last pins, excluding the end pins, is 1.27. The component is labeled with 'TAPE' and 'X3'. The pins are numbered 1 through 10. The distance between the center of the first and last pins, excluding the end pins, is 1.27.

Side view of the component. The overall height is 8.5 ± 0.3. The distance between the center of the first and last pins is 5.4. The distance between the center of the first and last pins, excluding the end pins, is 2.30. The component is labeled with 'X3' and '0.1MAX A'. The pins are numbered 1 through 10. The distance between the center of the first and last pins, excluding the end pins, is 2.30.

P.C.B. LAYOUT. The overall width is 1.27. The distance between the center of the first and last pins is 0.76. The distance between the center of the first and last pins, excluding the end pins, is 6.3. The component is labeled with 'X3' and '0.1MAX A'. The pins are numbered 1 through 10. The distance between the center of the first and last pins, excluding the end pins, is 6.3.

P. C. B LAYOUT

SCHEMATIC. The diagram shows 10 pins, numbered 1 through 10, connected to a common ground symbol. The pins are arranged in a row, with the ground symbol connected to the bottom of each pin.

SCHEMATIC

